



- NOTES: (Unless Otherwise Specified)
- [1] RF CONNECTORS ARE SMA, 2.92mm OR 1.85mm FEMALE.
 - [2] ONLY USED ON PACKAGE NUMBERS ENDING IN "D".
 - [3] CONNECTOR DIMENSIONS: SMA & 2.92mm FEMALE ARE .38". 1.85mm FEMALE IS .46".

Standard Outline Drawing for Cases with Female Connectors. Male Connectors available upon request. Waveguide options are available for Products operating >18 GHz

PACKAGE#	DIM "A"	DIM "B"
_F03__F_	.750	.600
_F04__F_	.950	.800
_F05__F_	1.150	1.000
_F06__F_	1.350	1.200
_F07__F_	1.550	1.400
_F08__F_	1.750	1.600
_F09__F_	1.950	1.800
_F10__F_	2.150	2.000
_F11__F_	2.350	2.200
_F12__F_	2.550	2.400
_F13__F_	2.750	2.600
_F14__F_	2.950	2.800
_F15__F_	3.150	3.000

Case Outline Example

Input RF Connector:	Function:	Output Connector
S=SMA	A=Amplifier	Type:
K=2.92mm	M=Multiplier	M=Male
V=1.85mm		F=Female

SF03ASFS

Input Connector Type:	Output RF Connector:	Bias Pin Configuration:
M=Male	S=SMA	S=Single Bias
F=Female	K=2.92mm	D=Dual Bias
	V=1.85mm	