



DRO TEST DATA SHEET

Model Number N06-1350 DC Power: +12.0 Volts
 S/N: 1001 @ 125 mA,
 Case Temp +25°C Spec. 120 mA typ.

| Freq. Out GHz | Voltage Tuning Range | Phase Noise | Power Out dBm | VSWR Out |
|------------------|-------------------------|----------------|------------------|-------------|
|------------------|-------------------------|----------------|------------------|-------------|

@10KHz
dBc/ Hz

| | | | | |
|----------------|------|---------|----------|----------------------|
| Start 13.997 2 | 2.0 | | Min +5.0 | Min 2.0:1 |
| Stop 14.002 8 | 18.0 | Max -74 | | |

MAX.

Power Flatness
+/- N/A dB

Data

| | | | | |
|----------|-------|-----|------|-----|
| | | | | |
| 13.997 2 | 6.32 | | 16.7 | 1.7 |
| 14.000 0 | 9.66 | -82 | 16.7 | 1.7 |
| 14.002 8 | 13.69 | | 16.7 | 1.7 |

Min/Max Data

| | | | |
|-----------|---------|----------|---------|
| Min 6.32 | | Min 16.7 | Min 1.7 |
| Max 13.69 | Max -82 | Max 16.7 | |

Power Flatness
+/- 0.0 dB

Tested By: [Signature] Date: 2/20/07 QA By: [Signature] Date: 2/21/07